

GyroTracer™



NO DRIFT ACCUMULATION.
ACCURATE TO 0.1%
OF TOTAL DEPTH



Continuous mode
registers data points
at every centimeter

www.sptab.com | sales@sptab.com



Specifications

Performance

Inclination accuracy	± 0.05°
Positional accuracy	< 0.1%* (Continuous mode NS, EW and TVD)
Gravity toolface accuracy	± 0.1° for inclination > 3°
Gyro toolface accuracy	± 1°
Repeatability azimuth	± 0.3°
Maximum Survey speed	150m/min (492ft/min)

*Subject to the well profile

Operation

Operating range	0° - 180° (from vertical)
H2S Resistant	Yes
Shock resistance	2000g 1ms
Battery	Li-ion rechargeable

Software

Export format	PDF, Excel, CSV, LAS
Survey report	Generate at any interval
Graphic generation	2D, 3D

GyroTracer 105°C

Pressure rating	10,000psi
Temperature rating	Up to 105°C (221°F)
Overall length (Telemetry, Real Time)	1250mm (49.21")
Overall length (Battery, Memory)	1635mm (64.37")
Diameter	42mm (1.65")
Weight	8kg (17.6lbs)

GyroTracer 150°C

Pressure rating	15,000psi
Temperature rating	Up to 150°C (302°F)
Heat shield length	2040mm (80.32")
Diameter	48mm (1.88")
Weight	12kg (26.5lbs)

GyroTracer 205°C

Pressure rating	20,000psi
Temperature rating	Up to 205°C (401°F)
Heat shield length	2800mm (110.24")
Diameter	49.5mm (1.94")
Weight	18kg (39.6lbs)

Maintain accuracy in all environments

All measurements are in reference to geographic north. Unlike other downhole survey tools, the *GyroTracer™* is not affected by magnetic interference. It can be run inside casing, tubing, drill pipe, and magnetically disturbed ground.

Versatile tool with multiple applications

The *GyroTracer™* can be run in a variety of situations from shallow to deep wellbore surveying. Use in continuous mode, single-shot/multi-shot, slim hole casing, orientation, whipstock kick-off and downhole motor orientation.

High pressure/high temperature (HP/HT) version available

Designed to function at full capacity in the harshest low/high temperature applications and environments. Built inside a Thermal Flask with continuous surveying capability at high latitudes or inclinations with no accuracy degradation.

For more information

Contact us at sales@sptab.com or www.sptab.com

EUROPE

Sweden (HQ)
+46 (8) 590-733-10
Spain
+34 (952) 179 918
Ukraine
+38 (067) 562 91 69

AUSTRALIA

Sydney (Australia)
+44 7508 835 893

NORTH AMERICA

Canada
+1 (877) 594-4633
Mexico (North)
+52 (662) 110-0219
+52 (662) 229-4755
Mexico (South)
+52 (662) 430-7255

USA
Mining Operation
+1 (602) 824 09 72
+1 (602) 824 09 79
Oil & Gas Operation
+1 (281) 460 55 08

SOUTH AMERICA

Argentina
+54 (9) 261-6231542
Brazil
+55 (31) 99625-4379
Chile (Santiago)
+56 (9) 953 937 90
Colombia
+57 (317) 6451026

Ecuador
+593 (99) 200 1060
+593 (98) 948 6928
Peru
+51 (962) 203 282

Africa

South Africa
+27 61 511 9401

ASIA-PACIFIC

Armenia
+374 (77) 815 683
Indonesia
+62 821 9100 651
Russia (Ufa)
+7 (347) 216 30 87
+7 (917) 342 83 15